

ATTACHMENT CHAIN















Our Rapid Response Program Delivers Your Solution

STANDARD		WIDE-CONTOUR		DOUBLE-PITCH	
DRIVES	PITCH	DRIVES	PITCH	DRIVES	PITCH
CHAIN NO.	P	CHAIN NO.	P	CHAIN NO.	P
40	0.500	40*	0.500	C2040	1.000
50	0.625	50*	0.625	C2050	1.250
60	0.750	60*	0.750	C2060H	1.500
80	1.000	80*	1.000	C2080H	2.000
100*	1.250			C2100H	2.500
120*	1.500			C2120H	3.000
140*	1.750			C2160H	4.000
160*	2.000				

* Attachment available on pin link plate only. If on roller link, contact your Drives representative.

DRIVES	OTHER TERMINOLOGY	DESCRIPTION
SINGLE PITCH & DOUBLE PITCH		
BA-1	B1 (one hole)	A1 Bent attachment, one side, one hole
BK-1	B2 (one hole)	K1 Bent attachment, both sides, one hole
SA-1	S1 (one hole)	M35 Straight attachment, one side, one hole
SK-1	S2 (one hole)	M1 Straight attachment, both sides, one hole
D-1	E-1	One extended pin
D-3	E-2	Two extended pins
DOUBLE PITCH		
BA-2	B1 (two holes)	A2 Bent attachment, one side, two holes
BK-2	B2 (two holes)	K2 Bent attachment, both sides, two holes
SA-2	S1 (two holes)	M35-2 Straight attachment, one side, two holes
SK-2	S2 (two holes)	M2 Straight attachment, both sides, two holes

SINGLE PITCH AND WIDE CONTOUR		
WBA-1	WCB1 (one hole)	WA1 Wide contour, bent attachment, one side, one hole
WBA-2	WCB1 (two holes)	WA2 Wide contour, bent attachment, one side, two holes
WBK-1	WCB2 (one hole)	WK1 Wide contour, bent attachment, both sides, one hole
WBK-2	WCB2 (two holes)	WK2 Wide contour, bent attachment, both sides, two holes
WSA-1	WCS1 (one hole)	WM35 Wide contour, straight attachment, one side, one hole
WSA-2	WCS1 (two holes)	WM35-2 Wide contour, straight attachment, one side, two holes
WSK-1	WCS2 (one hole)	WM-1 Wide contour, straight attachment, both sides, one hole
WSK-2	WCS2 (two holes)	WM-2 Wide contour, straight attachment, both sides, two holes

	BA-1 Bent attachment, single pitch, one side, one hole	
	WBK-2 Bent attachment, single pitch, wide contour, both sides, two holes	
	SA-1 (Roller Link) Straight attachment, single pitch, one side, one hole	
	WSA-2 Straight attachment, single pitch, wide contour, one side, two holes	
	SK-1 (Roller Link) Straight attachment, single pitch, both sides, one hole	
	D-1 Single pitch, one pin extended	
	Oversized Rollers Double pitch, oversized rollers	

Standard: • Carbon Steel (CS) • Stainless (AS)

- Available Options:**
- Corrosion resistant - Silver Shield CR[®] (CR) or Nickel Plated (NP).
 - Increased wear life and lower maintenance - Extended Life CHP[®] Series (CH).
 - Quantity minimums apply for stainless steel material.
 - Oversized rollers - material options - Delrin[®] and Celcon.

2-5 Working Days

SIZE	QTY.	MATERIAL
40, 50, 60, 80	Up to 100 feet	CS AS
C2040, C2050, C2060H, C2080H	Up to 100 feet	CS AS
100, 120, 140, 160	Up to 100 feet	CS --

6-12 Working Days

SIZE	QTY.	MATERIAL
40, 50, 60, 80	Up to 500 feet	CS AS
C2040, C2050, C2060H, C2080H	Up to 500 feet	CS AS
100, 120, 140, 160	Up to 500 feet	CS --

■ **Special MTO chains available.** For special lengths and types of attachment chains, including Silver Shield CR[®] (CR), Nickel Plated (NP), 316 Stainless Series (NS), 304 Stainless series (PS) Extended Life CHP[®] (CH) and Silver Shield (CR) with Extended Life CHP pins (CC), standard delivery is 4-6 weeks. Contact your Drives representative for more information, including specific shipment delivery dates.

AVAILABLE OPTIONS INCLUDE MATCHING AND TAGGING TO THREE CLASSIFICATIONS:

- **CLASS 1** - Ensures the longest and shortest chain in a set do not vary by more than 0.030" (0.76mm) per any given length.
- **CLASS 2** - Ensures the longest and shortest chain in a set do not vary by more than 0.020" (0.51mm) per any given length.

For more details of our matching and tagging process please reference the Drives catalog (order no. 10910).