

CUT-TO-LENGTH (CTL) PROGRAM

HIGH-PERFORMANCE STANDARD CHAIN TAILORED TO YOUR APPLICATION

Diamond-Drives by Timken has enhanced its Cut-to-Length (CTL) program to better serve you. Now, you can streamline your operations by ordering standard chain sizes precisely cut to your required lengths.

CTL CHAIN DELIVERED IN 6-10 DAYS

Stay on schedule with reliable service and timely delivery of cut-to-length standard chains, manufactured to exacting dimensional standards for industry-leading performance.

CHOOSE FROM THE FOLLOWING PRODUCT OFFERINGS:

- Drives® ASME/ANSI Standard Series Chain and Double-Pitch Chain
- Constructed With Carbon Steel
- Single and Double-Strand, Riveted
 - Select Sizes Available Cottered
- Customized to Even and Odd Lengths
 - Even Lengths: Includes a Connecting Link
 - Odd Lengths: Includes a Connecting Link and Offset Link

NOMENCLATURE

DRV	35	1	R	136	CTL
BRAND	CHAIN SIZE	# OF STRANDS	PIN TYPE	# OF PITCHES	ALL CTL PART NUMBERS END IN "CTL"

Offered in Select Sizes*				
Chain Size				
Riveted	35-1R	35-2R	40-1R	40-2R
	41-1R	50-1R	50-2R	60-1R
	60-2R	60H-1R	80-1R	80-2R
	80H-1R	100-1R	100-2R	100H-1R
	120-1R	120H-1R	140-1R	140H-1R
Cottered	80-1C	80HZ-1C	100-1C	100HZ-1C
	120-1C	120HZ-1C	140-1C	
High Strength	60HZ-1R	80HZ-1R	80HZ-1C	100HZ-1R
	100HZ-1C	120HZ-1R	120HZ-1C	140HZ-1R
Double Pitch	A2040-1R	C2040-1R	A2050-1R	C2050-1R
	C2060H-1R	C2080H-1R		

*Additional sizes will be offered to the cut-to-length program in the future

Pitches-to-Feet Cheat Sheet		
Chain Size	Pitch (Inch)	Pitches Per Foot
35	3/8	32
40	1/2	24
41	1/2	24
50	5/8	19.2
60	3/4	16
80	1	12
100	1 1/4	9.6
120	1 1/2	8
2040	1	12
2050	1 1/4	9.6
2060	1 1/2	8
2080	2	6