

# PART NUMBER CHEAT SHEET



## DIAMOND BRANDS

- DMD – Diamond (Most Common)
- DLR – Duralube® LIVE

## DRIVES BRANDS

- DRV – Drives (Most Common)
- EL – Drives Element®

1, 2, 3 etc. Number of Stands in a Chain

R = Riveted

C = Cotter

Attachment Spacing

Strand Length in Pitches

**DRV-80H-1RNPBK1-2P120**

## DIAMOND BRANDS

- Blank = Carbon Steel
- NP = Nickel Plated
- ZN = Diamond ACE®
- AP = Stainless Steel with 600SS Pins
- AU = 300SS Stainless Steel
- EH = EHT Chain

## DRIVES BRANDS

- Blank = Carbon Steel
- NP = Nickel Plated
- CR = Silver Shield CR®
- CC = Silver Shield CR® with Extended Life CHP® Pins
- AS = Stainless Steel with 600SS Round Parts
- PS = 300SS Stainless Steel
- NS = 316SS Stainless Steel
- CD = Extended Life CHP® with Hot Dip Lubricant

## STANDARD ATTACHMENTS

- BA1
- BA2
- BK1
- BK2
- SA1
- SA2
- SK1
- SK2
- D1
- D3
- WBA1
- WBA2
- WBK1
- WBK2
- WSA1
- WSA2
- WSK1
- WSK2

Note: Drives wide contour attachments are not available in sizes 35 and 100.

ANSI Chain Number	Pitch (Inches)
25	0.25
35	0.375
40	0.50
50	0.625
60	0.75
80	1.00
100	1.25
120	1.50
140	1.75
160	2.00
180	2.25
200	2.50
240	3.00

## DIAMOND BRANDS

- H – Heavy Series
- HS – Heavy Series High Strength
- S – High Strength
- XLO – Ring Leader™ XLO O-Ring

## DRIVES BRANDS

- H – Heavy Series
- HZ – Heavy Series High Strength
- Z – High Strength